

## Gauge Cross Reference - Cast Aluminum Case Industrial Gauge (Dry)

	Terice	Wika	U.S. Gauge	Ashcroft	Weksler	Weiss
Model	<b>500 XB</b> <b>500 XSS</b>	No exact equal Front Flange Hinged Ring Case ONLY 232.25HR 212.25HR	P-5801 = 500XB	1010A 1010 S	AA14/16/1 8	UG - 1 UG-2
Sizes	<b>4-1/2"</b> <b>6"</b> <b>8-1/2"</b> <b>12"</b>	4-1/2" 6"	3-1/2" 4-1/2" 6"	4-1/2" 6" 12" (S only)	4-1/2" - 14/44 6" - 16/46 8-1/2" - 18/48 12" - 49	3-1/2" 4-1/2" 6" 8-1/2"
Wetted Parts	<b>500 XB - Bronze T/S</b> <b>500 XSS - 316 SS T/S</b>	212.25HR Copper Alloy 232.25HR - 316 SS	Phosphor Bronze	A- Brass/Phosp hor Bronze S- 316 SS	14/16/18 - Phosphor Bronze/For ged Brass 44/46/48/4 9 - 316 SS	UG-1 - Bronze Tube/Brass Socket UG-2 - 316 SS T/S
Movement	<b>Stainless Steel</b>	Stainless Steel	Brushed Dis- similar Metal	SS Movement	300 SS	SS Movement
Connectio n	<b>1/4" NPT</b> <b>1/2" NPT</b>	1/4" NPT - 4- 1/2" Only 1/2" NPT	1/4" NPT	1/4" NPT 1/2" NPT - (S Only)	1/4" NPT 1/2" NPT	1/4" NPT 1/2" NPT
Case	<b>Cast Aluminum Back Flanged Std.</b>	Black Painted Aluminum	Die Cast Aluminum Back Flanged	Aluminum	4-1/2" - Polypropyl ene 6" - Aluminum 8-1/2" - Phenol 12" - Aluminum	Aluminum
Window	<b>Clear Glass</b>	Flat Glass	3-1/2" - Plain Glass 4-1/2", 6" - Acrylic	Glass	Glass	Glass

Accuracy	<b>±0.5% Full Scale</b>	±0.5% FS	3-1/2" ±1.5/1/1.5% 4-1/2" Or 6" - ±1.0% Span	±1.0% FS	±0.5% FS	±0.5% FS
----------	-------------------------	----------	---	----------	----------	----------