

Gauge Cross Reference - Industrial Gauge (Liquid Fillable)

	Trerice	Wika	U.S. Gauge	Ashcroft	NoShok	McDaniel
Model	700B 700SS 700M	212.54 (2.5", 4") 232.54 (2.5", 4") 212.20 (6" only) 232.50 (6" only)	6562 6566	1009-SW (2.5", 3.5", 100mm) 1009-A (4.5", 6") 1009-S (4.5", 6")	100 Series 400 Series	S Q3 K E / G F / H
Sizes	2-1/2" 4" 6"	2-1/2" 4" 6"	6562-2-1/2" 6566 - 4"	2-1/2" 3-1/2" 100mm (4") 4-1/2" 6"	100 - 4"(40.105) 400 - 2- 1/2"(25.400) 400 - 4"(40.400) 400 - 6"(60.400)	S - 1-1/2" Q3 - 2" K - 2-1/2" E / G - 4" F / H - 6"
Wetted Parts	700B - Copper Alloy 700SS - 316 SS T/S 700M - Monel T/S	212.54 / 212.20 Copper Alloy 232.54/232.50 316 SS	316L SS	1009-SW 316 SS (Welded) 1009-A Bronze/Brass 1009-S 316 SS T/S	100 - Bronze 400 - SS	316 Stainless Steel
Movement	Stainless Steel	212.54 / 212.20 Copper Alloy 232.54/232.50 316 SS	304 SS	304SS	100 - Brass / Nickel 400 - SS	316 Stainless Steel
Connection	2-1/2" - 1/4" NPT 4", 6" - 1/4" or 1/2" NPT	2-1/2" - 1/4" NPT 4" - 1/4" or 1/2" NPT 6" - 1/2" NPT	6562 1/4" NPT 6566 - 1/2" NPT	2.5", 3.5" - 1/4" or 1/2" NPT 4.5", 6" - 1/4" or 1/2" NPT 100mm - 1/2" only	100 - 1/4" NPT 400 - 2-1/2" - 1/4" NPT 400 - 4" & 6" - 1/2" NPT	S, Q3, K - 1/8" NPT S, Q3, K, E, F - 1/4" NPT G, H - 1/2" NPT
Case	304 SS	304 SS	304 SS	304 SS	100 - Brass / Nickel-Silver 400 - SS	304 SS
Window	Laminated Safety Glass	212.54, 232.54, 232.50 Lam. Safety Glass 212.20 Acrylic	6562 - Polycarbonate 6566 - Acrylic	Polycarbonate (2.5", 3.5") Shatterproof Glass (100mm) Glass (4.5", 6")	100 - Plexi- Glass 400- 2.5" Trogimide 4" Instrument Glass 6" Lam. Safety	1-1/2" Lexan 2", 2-1/2", 4", 6" Lam. Safety Glass

					Glass	
Accuracy	±1.0% Full Scale	2-1/2" ± 1.5% FS 4", 6" ± 1.0% FS	6562 ± 1.6% FS 6566 ± 1.0% FS	±1.0% FS	100 ± 1.0% 400 - 2-1/2" ± 1.5% 4", 6" ± 1.0%	S ± 1.5% Q3, K - ± 1.0% E/G, F/H - ± 0.5%