

## Gauge Cross Reference - Utility Gauge D80 Series stainless steel case (Liquid Filled)

|              | Trerice   | Wika  | U.S. Gauge   | Ashcroft   | NoShok   | McDaniel   |
|--------------|---|---|--|--|--|--|
| Model        | <b>D821<br/>D83</b>   | 213.53<br>233.53                                  | 550<br>555<br>545<br>546                                   | 1008AL<br>1008SL   | 900<br>Series<br>500<br>Series                                 | T6<br>J6<br>K9GF<br>F9GF/G9GF                                      |
| Sizes        | <b>2-1/2"<br/>4"</b>  | 2-1/2"<br>4"                                      | 2-1/2" -<br>550/555<br>4" - 545/546                        | 1.5" (1008SL<br>Only)<br>2" (1008SL Only)<br>2-1/2"<br>4"          | 2-1/2" -<br>(25.901,<br>25.500)<br>4" -<br>(40.901,<br>40.500) | 2" - T6<br>2-1/2", J6, K9GF<br>4" F9GF, G9GF                       |
| Wetted Parts | <b>D821 Bronze<br/>Tube/<br/>Brass Socket<br/>D831 316 SS</b> | 213.53 -<br>Copper<br>Alloy<br>233.53 -<br>316 SS | 555/545/546 -<br>Brass T/S<br>550 - 316 SS                 | 1008AL - Brass<br>T/S<br>1008SL - SS T/S                           | 900 -<br>Phosphor<br>Bronze<br>500 - 316<br>SS                 | T6, J6<br>Bronze/Brass T/S<br>K9GF, F9GF,<br>G9GF - 316 SS         |
| Movement     | <b>D821 Brass<br/>D831 316 SS</b>                             | 213.53 -<br>Copper<br>Alloy<br>233.53 -<br>316 SS | 555/545/546 -<br>Brass T/S<br>550 - 304 SS                 | 1008AL - Brass<br>1008SL - 300<br>Series SS                        | 900 -<br>Brass<br>500 -<br>Stainless<br>Steel                  | T6, J6 Brass<br>K9GF, F9GF,<br>G9GF -<br>316 SS                    |
| Connection   | <b>1/4" NPT</b>   | 1/4" NPT<br>1/2" NPT<br>(4" only)                 | 1/4" NPT   | 1/8" NPT (1.5",<br>2" only)<br>1/4" NPT<br>1/2" NPT - (4"<br>only) | 1/4" NPT<br>1/2" NPT<br>500 (4"<br>only)                       | 1/8" NPT (T6, J6<br>only)<br>1/4" NPT<br>1/2" NPT - (G9GF<br>only) |
| Case         | <b>304 SS</b>   | 304 SS  | 304 SS   | 304 SS   | 304 SS   | 304 SS   |
| Window       | <b>2-1/2" - Styrene<br/>Acrylonite<br/>4" - Grilamid</b>      | 2-1/2" -<br>Polycarbon<br>ate<br>4" - Acrylic     | 2-1/2" -<br>Polycarbonate<br>" - Laminated<br>Safety Glass | 1.5", 2" - Glass<br>2-1/2", 4" -<br>Polycarbonate                  | 900 -<br>Plexiglas<br>s  | Glass 4CTA<br>Lexan 4CTS   |

|          |                         |  |                                   |          |                                      |  |
|----------|-------------------------|--|-----------------------------------|----------|--------------------------------------|--|
| Accuracy | <b>±1.5% Full Scale</b> | 213.53 ±<br>1.5% FS<br>233.5 - 2-<br>/2" ± 1.5%<br>FS<br>" ± 1% FS | 2-1/2" ± 1.6%<br>FS<br>4" ± 1% FS | ± 3/2/3% | 2-1/2" ±<br>1.5% FS<br>4" ± 1%<br>FS | T6, J6 ± 3/2/3%<br>K9GF, F9GF,<br>G9GF -<br>± 2/1/2% |
|----------|-------------------------|--|-----------------------------------|----------|--------------------------------------|--|